



PERFECT FIT™


SINGLE FIXTURE SERIES by Northwest LED Lighting

Job Name
Notes


Professional quality, customized LED light fixtures without the custom price!

Fixture Options (H x W)

S = Single 5/8" x 3/4"



Q = Recessed Single
 5/8" x 3/4" x 1" flange
 Inset depth = 1/2"



* Fixtures shown with frosted lens

Features



- ETL certified fixtures conform to UL Std 2108 and NEC requirements.
- Color Rendering Index (CRI) of 93 or above. Brings out true colors
- Fixtures require a separate LED driver and are dimmable when powered with an approved dimmable driver.
- Custom fabricated in the USA in lengths from 4-inches up to 16 feet.
- Miniature hardwired fixtures are easily hidden under or inside cabinets, and do not require special cables or connectors.
- 5/8" deep housing minimizes LED imaging on the lens.
- 2-year warranty when powered with a Northwest LED approved driver. Ask for details.

Diffuser Lens Options

Standard Lenses

Frosted (f) - produces a softer, slightly warmer diffused light and is preferred with reflective surfaces to minimize glare and reflection.

Prismatic (p) - produces a brighter, slightly whiter light and is preferred where maximum light output is desired and the fixture is hidden from normal view.

Specialty Lenses (select models only)

Focus Lens (x) - allows the light to be "focused" into a narrow 30 degree beam for wall wash effects.

Opal (o) - heavily frosted for maximum light diffusion (reduces light output).

Color Options

2700 k	Incandescent White
3000 k	Halogen White
4000 k	Natural White

Single fixture with Focus Lens



Brightness Options	Voltage DC	Watts/ Ft.	LEDs/ Ft.	Lumen/ Ft.
Soft (SO)	12	1.5	18	130
Standard (ST)	12	2	9	180
Medium Bright (MB)	12/24	2.9	36	260
Bright (BR)	12	4	18	350
Extra Bright (XB)	12/24	4.4	36	400

Ordering Information

All Perfect Fit™ fixtures come standard with a single 24-inch long lead, and 3M double stick foam mounting tape. Fixtures may be ordered in 3 different color temperatures and in the brightness levels shown above. Fixtures may be ordered with extra long leads, leads on both ends, or interconnected with a short "jumper" to allow fixtures to be mounted around corners.

Example: LinF12-Sf-BR-30k-34-L36

Model	Lens	Brightness	Color Temp	Fixture Length In Inches	Options
LinF12-S	f = frosted	SO=Soft	27k=2700k	4 (minimum)	L=lead length (other than 24" std.)
LinF12-Q	p = prismatic x = focus o = opal	ST =Standard MB=Med Bright BR =Bright XB=Extra Bright	30k=3000k 40k=4000k	to 192 (maximum)	S=second lead length I=interconnect MC= mounting clips RC=rotating clips
LinF24-S LinF24-Q	f, p, x, o	MB, XB	27k, 30k	4 to 192	L, S, I, MC, RC



1404 Riverside Dr., Ste. F, Mount Vernon, WA 98273 • 360.422.5387 • www.NorthwestLED.com • info@northwestLED.com

