


PERFECT FIT™

LED RIBBON by Northwest LED Lighting



Cove Lighting using LinR12-ST-27k

Color Temperature *

2700 k	Incandescent White
3000 k	Halogen White
4000 k	Natural White
RGB	Color Adjustable

Professional quality, energy efficient ribbon light available in multiple color and brightness options to meet your lighting needs.

Our LED ribbon is dimmable, low voltage lighting that is extremely thin and flexible, making it suitable for use in areas with minimal clearance, curved areas and more! Comes standard in 16.4 foot rolls.

Features

- Color Rendering Index (CRI) of 93 or above - Brings out true colors.
- 3M Adhesive backing adheres to most surfaces.
- White, 2-foot leads on both ends of roll for easier installation.
- UL certified-conforms to UL Std. 2108.
- Dimmable (when powered with approved dimmable driver).
- Damp Rated (IP65) options available.
- Easily cut to required length.
- Available in custom lengths or with custom lead lengths.

Style & Brightness	Part # 12=12V 24=24V	Color	Lumens/ Ft.	Watts/ Ft.	Watts/ Roll	# LEDs per roll	Cut interval	Typical Uses
Dry IP20 Soft output	LinR12-SO	27k 30k 40k	130	1.5	24	300	2"	Toe kick, cove lighting, small cabinets
Dry IP20 Standard output	LinR12-ST	27k 30k 40k	180	2	33	150	4"	Accent lighting, cove lighting, in-cabinet, wine cellars, closets
Dry IP20 Med Bright output	LinR12-MB	27k 30k 40k	260	2.9	48	600	1"	Task and accent lighting where close LED spacing is desired
Dry IP20 Bright output	LinR12-BR	27k 30k 40k	350	4	65	300	2"	Task and accent lighting where more light is desired
Dry IP20 Extra Bright output	LinR12-XB	27k 30k 40k	400	4.4	72	600	1"	Task and accent lighting where more light is desired
Dry IP20 Dual Bright output	LinR24-DB	27k 30k 40k	700	5.9	96	1200	2"	Area, task and up lighting
Dry IP20 RGB-color change	LinR12-RGB	N/A	N/A	4.4	72	300	4"	Color adjustable for special effect
Dry IP20 RGBW-color change	LinR12-RGBW	27K	180	4.4	72	300	4"	Color adjustable + white combo
Damp IP65 Same as above	Add IP65 to above part number		Same as above	Same as above	Same as above	Same as above	Same as above	Damp locations, outdoor soffits etc.



Example part numbers

LinR12-SO-27k = Ribbon, 12VDC, Soft output, 2700k

LinR12-BR-30k-IP65 = Ribbon, 12VDC, Bright output, 3000k, Damp Rated

* Other colors available by special order. Please call for details and ordering instructions.