

PERFECT FIT™


SINGLE Fixture Series by Northwest LED

Job Name
Notes


Professional quality, custom LED light fixtures without the custom price!

Housing Options (H x W)

S = Single 5/8" x 11/16"



Q = Recessed Single 5/8" x 11/16" x 15/16" flange Inset depth = 1/2"



Fixtures shown in silver w/frosted lens

Features



- ETL certified fixtures conform to UL Std 2108 and NEC requirements.
- Color Rendering Index (CRI) of 95 or above. Brings out true colors
- Fixtures require a separate LED driver and are dimmable when powered with an approved dimmable driver.
- Custom fabricated in the USA in lengths from 4-inches up to 16 feet.
- Miniature hardwired fixtures are easily hidden under or inside cabinets, and do not require special cables or connectors.
- 5/8" deep housing minimizes LED imaging on the lens.
- 2-year warranty when powered with a Northwest LED approved driver. Ask for details.

Diffuser Lens Options

Standard Lenses

Frosted (f) - produces a softer, slightly warmer diffused light and is preferred with reflective surfaces to minimize glare and reflection.

Prismatic (p) - produces a brighter, slightly whiter light and is preferred where maximum light output is desired and the fixture is hidden from normal view.

Specialty Lenses (select models only)


Focus Lens (x) - allows the light to be "focused" into a narrow 30 degree beam for wall wash effects.

Opal (o) - heavily frosted for maximum light diffusion (reduces light output).

Single fixture with Focus Lens



Finish Options



Brightness Options	Voltage DC	Watts/ Ft.	LEDs/ Ft.	Lumen/ Ft.
Soft (SO)	12	1.5	18	130
Standard (ST)	12	2	9	180
Medium Bright (MB)	12/24	2.9	36	260
Bright (BR)	12	4	18	350
Extra Bright (XB)	12/24	4.4	36	400

LED Color Options

2400 k	Very Warm White (MB only)
2700 k	Incandescent White
3000 k	Halogen White
4000 k	Natural White

Ordering Information

All SINGLE series fixtures come standard with "Silver" finish, a single 2 foot long lead and 3M foam mounting tape. Please specify the housing style, color temperature, brightness level, and finished length for each fixture. Fixtures may *optionally* be ordered with extra long leads, leads on both ends, interconnected with a short "jumper" to allow fixtures to be mounted around corners or with mounting clips. Finish options other than silver generally require additional lead time. Please call for availability and pricing.

Example: LinF12-Sf-BR-30k-34-L36

Model	Lens	Brightness	Color Temp	Fixture Length In Inches	Options
LinF12-S	f = frosted	SO=Soft	24k=2400k MB only	4 (minimum)	L=lead length (other than 2' std.)
LinF12-Q	p = prismatic	ST =Standard	27k=2700k	to	S=second lead length
	x = focus	MB=Med Bright	30k=3000k	192 (maximum)	I=interconnect
	o = opal	BR =Bright	40k=4000k		MC= mounting clips
		XB=Extra Bright			RC=rotating clips
LinF24-S	f, p, x, o	MB, XB	27k, 30k	4 to 192	L, S, I, MC, RC
LinF24-Q					

Northwest LED