

# PERFECT FIT

Electronic LED Drivers to power Perfect Fit Fixtures & Ribbon

Job Name
Notes

**SC Series** - Our most versatile dimmable drivers. Compact, hardwired and compatible with most ELV / Triac / MLV & incandescent dimmer switches.\* UL Listed, Dry or Damp location rated. 100 - 277 VAC input. Integrated coated metal junction box case with 6 wiring knock-outs. Overload, overcurrent, and temperature protected. 10% minimum load required.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Class 2	Case Color
SC-KVF12030-TDWJ	SC-KVF24030-TDWJ	30	6.5 x 3.5 x 1"	Y	Black
SC-KVF12060-TDWJ	SC-KVF24060-TDWJ	60	7.5 x 3.5 x 1"	Y	Black
NA	SC-KVF24096-TDWJ	96	8.5 x 3.5 x 1.75"	Y	Black
SC-KVF12100-TDWJ	NA	100	8.5 x 3.5 x 1.75"	N	Black
SC-KVF12150-TDWJ	SC-KVF24150-TDWJ	150	10.25 x 4 x 1.75"	N	Black
SC-KVF12200-TDWJ	SC-KVF24200-TDWJ	200	10.25 x 4 x 1.75"	N	Black
SC-KVF12300-TDWJ	SC-KVF24300-TDWJ	300	11 x 4.25 x 1.75"	N	Black



**MX Series** - High performance & economical dimmable drivers. Hardwired and compatible with most Triac / MLV & incandescent dimmer switches.\* ETL listed, IP20 indoor rated. 120 VAC input. Integrated coated metal junction box case with 6 wiring knock-outs. Overload, overcurrent, and temperature protected. 5% minimum load required.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Class 2	Case Color
ZV025012TK2AJ	ZV025024TK2AJ	25	13.75 x 3 x 1"	Y	White
ZV050012TK2AJ	ZV050024TK2AJ	50	13.75 x 3 x 1"	Y	White
ZV060012TK2AJ	ZV060024TK2AJ	60	13.75 x 3 x 1.5"	Y	White
NA	ZV096024TK6AJ	96	15 x 3 x 2.25"	Y	Black
ZV100012TK6AJ	NA	100	15 x 3 x 2.25"	N	Black
ZV150012TK6AJ	ZV150024TK6AJ	150	16 x 3.375 x 2.3"	N	Black
ZV200012TK6AJ	ZV200024TK6AJ	200	16 x 3.375 x 2.3"	N	Black



**BL Series** - Mini drivers designed to mount inside a junction box. Dimmable with ELV dimmer switches only. 120 VAC input.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Class 2	Style
EX95101-12VDC	EX95121-24VDC	60	1.375 x 1 x 3	Y	In Box



**Plug in Non-Dimmable** - UL listed plug-in style 12VDC transformers with short circuit, overload, and over-voltage protection

12 VDC Model #	24 VDC Model #	Wattage	Dimensions	Class 2	Style
SGA12U12-P1J	SGA12U24-P1J	12	1.8 x 2.5 x 1"	Y	Wall Wort
GST25U12-P1J	GST25U24-P1J	25	2 x 3 x 1.25"	Y	Wall Wort
GST40A12-P1J	GST40A24-P1J	40	1.875 x 4.75 x 1.25"	Y	Brick
GST60A12-P1J	GST60A24-P1J	60	1.875 x 4.75 x 1.25"	Y	Brick
GST90A12-P1M	GST90A24-P1M	90	2.25 x 5.625 x 1.25"	N/Y	Brick



**Hardwired Non-Dimmable** - Hardwired air cooled power supply in plastic case. LPV models are waterproof (IP67). All models except 100W are UL1310 rated. Not recommended for use in full sun light.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions	Class 2	Style
APV-35-12	APV-35-24	35	3.25 x 1.1875 x 2.25"	Y	Hardwired
LPV-20-12	LPV-20-24	20	4.5 x 1.0625 x 1.375"	Y	Hardwired-IP67
LPV-60-12	LPV-60-24	60	6.25 x 1.25 x 1.625"	Y	Hardwired-IP67
LPV-100-12	LPV-100-24	100	7.375 x 1.5 x 1.0625"	N/Y	Hardwired-IP67

