

PERFECT FIT

Electronic LED Drivers to power Perfect Fit Fixtures & Ribbon

Job Name
Notes

SC KVF Series - Our most popular dimmable drivers. Compact, hardwired and compatible with most ELV / Triac / MLV & incandescent dimmer switches.* UL Listed - dry, damp and wet location rated. 100 - 277 VAC input. Integrated coated metal junction box case with 6 wiring knock-outs. Overload, over-current, and temperature protected. 10% minimum load required. Flicker free, 0-100% dimming range. Multi-output class 2 models listed below.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Class 2	Case Color
SC-KVF-12030-TDWJ	SC-KVF-24030-TDWJ	30	6.5 x 3.5 x 1"	Y	Black
SC-KVF-12060-TDWJ	SC-KVF-24060-TDWJ	60	7.5 x 3.5 x 1"	Y	Black
NA	SC-KVF-24096-TDWJ	96	8.5 x 3.5 x 1.75"	Y	Black
SC-KVF-12100-TDWJ	NA	100	8.5 x 3.5 x 1.75"	N	Black
SC-KVF-12150-TDWJ	SC-KVF-24150-TDWJ	150	10.25 x 4 x 1.75"	N	Black
SC-KVF-12200-TDWJ	SC-KVF-24200-TDWJ	200	10.25 x 4 x 1.75"	N	Black
SC-KVF-12300-TDWJ	SC-KVF-24300-TDWJ	300	11 x 4.25 x 1.75"	N	Black

Multi-Output Class 2 Models

SC-KVF-C12180-TDWJ	N/A	180 (3x60)	11 x 4.25 x 1.75"	Y	Black
N/A	SC-KVF-C24192-TDWJ	192 (2x96)	11 x 4.25 x 1.75"	Y	Black
SC-KVF-C12300-TDWJ	N/A	300 (5x60)	12 x 4.25 x 1.75"	Y	Black
N/A	SC-KVF-C24192-TDWJ	288 (3x96)	13 x 4.25 x 1.75"	Y	Black

SC KVG Series - Our most versatile dimmable drivers. Compact, hardwired and compatible with most ELV / Triac / MLV & incandescent dimmer switches,* plus 0-10V and 1-10V dimming. UL Listed - dry and damp location rated. 100 - 277 VAC input. Integrated coated metal junction box case with 6 wiring knock-outs. Overload, over-current, and temperature protected. 10% minimum load required. Flicker free, 0-100% dimming range.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Class 2	Case Color
SC-KVG-12030-DWJ	SC-KVG-24030-DWJ	30	6.5 x 3.5 x 1"	Y	Black
SC-KVG-12060-DWJ	SC-KVG-24060-DWJ	60	7.5 x 3.5 x 1"	Y	Black
NA	SC-KVG-24096-DWJ	96	8.5 x 3.5 x 1.75"	Y	Black
SC-KVG-12100-DWJ	NA	100	8.5 x 3.5 x 1.75"	N	Black
SC-KVG-12150-DWJ	SC-KVG-24150-DWJ	150	10.25 x 4 x 1.75"	N	Black
SC-KVG-12200-DWJ	SC-KVG-24200-DWJ	200	10.25 x 4 x 1.75"	N	Black
SC-KVG-12300-DWJ	SC-KVG-24300-DWJ	300	11 x 4.25 x 1.75"	N	Black

MX Series - High performance & economical dimmable drivers. Hardwired and compatible with most Triac / MLV & incandescent dimmer switches.* ETL listed, IP20 indoor rated. 120 VAC input. Integrated coated metal junction box case with 6 wiring knock-outs. Overload, overcurrent, and temperature protected. 5% minimum load required.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Class 2	Case Color
ZV025012TK2AJ	ZV025024TK2AJ	25	13.75 x 3 x 1"	Y	White
ZV050012TK2AJ	ZV050024TK2AJ	50	13.75 x 3 x 1"	Y	White
ZV060012TK2AJ	ZV060024TK2AJ	60	13.75 x 3 x 1.5"	Y	White
NA	ZV096024TK6AJ	96	15 x 3 x 2.25"	Y	Black
ZV100012TK6AJ	NA	100	15 x 3 x 2.25"	N	Black
ZV150012TK6AJ	ZV150024TK6AJ	150	16 x 3.375 x 2.3"	N	Black
ZV200012TK6AJ	ZV200024TK6AJ	200	16 x 3.375 x 2.3"	N	Black

BL Series - Mini drivers designed to mount inside a junction box. Dimmable with ELV dimmer switches only. 120 VAC input.

12 VDC Model #	24 VDC Model #	Wattage	Dimensions (L x W x H)	Class 2	Style
EX95101-12VDC	EX95121-24VDC	60	3 x 1.375 x 1	Y	In Box

